



FICHA TECNICA MOTOVIBRADOR SERIE ADX M

Foot Mounted Vibration Motors

AVIBRO foot mounted vibration motors offer a full range of premium quality foot mounted vibrator motors that meet the needs of all industrial machinery where vibration power is required.

We declare that all our ADX series products comply with the essential health and safety requirements of the applicable EEC Directives (safety of machinery 2006/42/EC; and 2014/35/EU Low voltage directives) and are able to fulfill the requirements for free movement. *Declaration will lose its validity if there will be any change by product.

AVM AFV / AFV-EC / AFV-C AVM-D AVM-P Series vibration motors can be operated by variable Frequency inverters (VFD featured).

All series which starts with AVM code;

II2D Ex tb IIIC (T120 °C) Zone 21 Zone 22



Foot Mounted Vibration Motors Technical Specifications

Three-Phase Input Voltage:
For all ADX Series : Standart applications 50Hz 220 – 230/380-400 Volt or 60Hz 220-240/440-480 Volt
We are offering you different voltage and frequency on demand
APV series can be operated by electronic or electromechanic converters.

Frequency and Rotation per Minute (rpm)

For all ADX Series :

2 poles: 3000 rpm - 50 Hz 3600 rpm - 60 Hz

4 poles : 1500 rpm - 50 Hz 1800 rpm - 60 Hz

Foot Mounted Vibration Motors Adjusting Vibration Force

AVIBRO Vibration motors are designed for gaining most vibration according to working regime S1. Thanks to degrees on both end Masses from %0 to %100 you can adjust required vibration force. Eccentric masses on both side ends of shaft must be at same degrees.

AVIBRO Mechanical Protection

We declare that all our ADX series products comply with the essential health and safety requirements of the applicable EEC Directives (safety of machinery 2006/42/EC; and 2014/35/EU Low voltage directives) and are able to fulfill the requirements for free movement. *Declaration will lose its validity if there will be any change by product.

AVIBRO Inside of Electric Motor

We are highly aware of environmental pollution in our Planet. We are highly aware of environmental pollution in our Planet. For this reason, AVIBRO offers you more power compared to its competitors with the STATOR-ROTOR design created with the lowest loss silicon magnetic lamination sheets, while offering products with increased efficiency by reducing heating.

AVIBRO Vibration Motors Isolation Class

AVM series vibration motors have powerful standard H class insulation. On demand, you can choose a stronger insulation class. Eccentric weight covers, bearing covers and terminal covers are mechanically protected against external damage with o-ring seals. Inside the terminal box, it is protected by Epoxy resin against leakage and vibration. IP 65-7

AVIBRO Vibration Motors Environmental Working Temperature

For ADX Series -20 C° ile +40 C° (-4 F ile 104 C°)

AVIBRO Vibration Motors Thermal Protection

For ADX series products, we do not have a standard thermistor application. We offer 130 C PTC Application on AVM-P series products on demand.

AVIBRO Vibration Motors Body and Rotating Shaft

For ADX series, all other series and new products, stress analyzes are made on the product bodies and bearing covers on the 3D CAD program. Afterwards, we manufacture our 50 frame size body and bearing covers, our special alloy aluminum injection molding 60 and 110 structure size body and bearing covers from high resistant GGG 40 ductile cast iron. Our rotating shafts (rotor shaft) use NiCrMo special steel round raw material with high resistance to torsion and rupture with heat treatment.

AVIBRO Vibration Motors Painting

We use electrostatic epoxy powder paint in almost all of our ADX Series products.
Body color code: ORANGE
Covers color Code: ORANGE

AVIBRO Vibration Motors Bearing and Lubrication

AVIBRO vibrator motors use bearings with C4 backlash produced for long-lasting vibration in all standard products. Thus, we produce long-lasting vibration motors for our customers. For our vibration motor bearings, we use long-lasting, high-strength greases against high centrifugal forces, stress caused by vibration, and abrasions that may occur from loads on bearing internal grains. We use labyrinth type channels and oil seals to ensure that the grease runs in the bearings without any leakage.

AVIBRO Vibration Motors On Demand Manufacturing

We Offer

Pre-heaters
Stainless side covers Cr
Different foot-prints for your special applications

design productions