



FICHA TECNICA MOTOVIBRADOR SERIE AVM-M

Foot Mounted Vibration Motors

AVIBRO foot mounted vibration motors offer a full range of premium quality foot mounted vibrator motors that meet the needs of all industrial machinery where vibration power is required.

We declare that all our AVM-M series products comply with the essential health and safety requirements of the applicable EEC Directives (safety of machinery 2006/42/EC; and 2014/35/EU Low voltage directives) and are able to fulfill the requirements for free movement.

For All AVM series :

II2D Ex tb IIIC (T120 °C) Zone 21 Zone 22



Foot Mounted Vibration Motors Technical

Specifications

Single-Phase Input Voltage:

For All AVM series : Standart applications: 50Hz-100Hz 220-230 Volt or 60Hz-110*115 Volt We are offering you different voltage and frequency on demand

Frequency and Rotation per Minute (rpm)

For All AVM series :

2 poles : 3000 rpm- 50 Hz 3600 rpm- 60 Hz

4 poles : 1500 rpm- 50 Hz 1800 rpm- 60 Hz

Foot Mounted Vibration Motors Adjusting Vibration Force

AVIBRO Vibration motors are designed for gaining most vibration according to working regime S1. Thanks to degrees on both end Masses from 0 to 100 you can adjust required vibration force. Eccentric masses on both side ends of shaft must be at same degrees.

AVIBRO Mechanical Protection

We hereby declare that All APV Series goods are manufacturing in compliance with regulations envisioned by EEC(Machine directive 2006/42/EC Directive 2006/42/EC of the European Parliament and of the Council of 17 May 2006 on machinery, and amending Directive 95/16/EC (recast) AND 2014/35/EU Directive 2014/35/EU of the European Parliament and of the Council of 26 February 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of electrical equipment designed for use within certain voltage limits (recast). *Declaration will lose its validity if there will be any change by product.

AVIBRO Inside of Electric Motor

We are highly aware of environmental pollution in our Planet. We are highly aware of environmental pollution in our Planet. For this reason, AVIBRO offers you more power compared to its competitors with the STATOR-ROTOR design created with the lowest loss silicon magnetic lamination sheets, while offering products with increased efficiency by reducing heating.

AVIBRO Vibration Motors Isolation Class

AVM-M series vibration motors have powerful standard H class insulation. On demand, you can choose a stronger insulation class. On demand, you can choose a stronger insulation class. Eccentric weight covers, bearing covers and terminal covers are mechanically protected against external damage with o-ring seals. Inside the terminal box, it is protected by Epoxy resin against breakage against leakage and vibration. IP 65-7

AVIBRO Vibration Motors Environmental Working Temperature

For AVM-P Series -20 C +40 C (-4 F 104 F)

AVIBRO Vibration Motors Thermal Protection

For AVM-M series products, we do not have a standard thermistor application. We offer 130 C PTC Application on AVM-P series products on demand.

AVIBRO Vibration Motors Body and Rotating Shaft

For AVM-M series, all other series and new products, stress analyzes are made on the product bodies and bearing covers on the 3D CAD program. Afterwards, we manufacture our bodies in 10-30 sizes from special alloyed aluminum injection and our bearing covers from GGG 40 ductile cast iron. Our

rotating shafts (rotor shaft) use NiCrMo special steel round raw material with high resistance to torsion and rupture with heat treatment.

AVIBRO Vibration Motors Painting

We use electrostatic epoxy powder paint in almost all of our AVM-M Series products.
Body color code: ORANGE
Covers color Code: ORANGE

AVIBRO Vibration Motors Bearing and Lubrication

AVIBRO vibrator motors use bearings with C4 backlash produced for long-lasting vibration in all standard products. Thus, we produce long-lasting vibration motors for our customers. For our vibration motor bearings, we use long-lasting, high-strength greases against high centrifugal forces, stress caused by vibration, and abrasions that may occur from loads on bearing internal grains. We use labyrinth type channels and oil seals to ensure that the grease runs in the bearings without any leakage.

AVIBRO Vibration Motors On Demand Manufacturing

We Offer

Pre-heaters

Stainless side covers Cr

Different foot-prints for your special applications

design productions